



Codice Part number	
P34070 - 100	P34070 - 500
Per passare da N.C. a N.A. è sufficiente capovolgere il galleggiante The contact can be converted from N.C. to N.O. by rotating the float upside down	Contatto SPDT SPDT Contact
Il collegamento a terra deve essere garantito dal sistema di montaggio Grounding must be fasten by assembling system	

Per versioni personalizzate (lunghezza, temperatura > 100°C, ecc.) contattare Euroswitch.  
 Nel caso di connessioni non isolate devono essere prese le adeguate precauzioni per garantire la distanza minima di sicurezza tra i diversi morsetti.

*For customized version (length, temperature > 100°C, etc.) please contact Euroswitch.  
 When using non-insulated connections, the necessary precautions must be taken to ensure the minimum safety distance between the terminals.*

Impiego Use	<b>Oli minerali - Carburanti - Acqua</b> Mineral oils - Fuels - Water
Fissaggio Fixing	<b>1/8" gas conico</b> 1/8" gas conical
Stelo Stem	<b>Ottone</b> Brass
Galleggiante Float	<b>Nylon espanso (per pressioni &gt; di 1 bar si consiglia il galleggiante in NBR)</b> Foamed nylon (for pressure > 1 bar use NBR float execution)
Seeger	<b>Bronzo fosforoso</b> Phosphorous bronze
Connessione elettrica Electrical connection	<b>1000 mm Sez. 0,5 mm<sup>2</sup> PVC</b> 1000 mm section 0,5 mm <sup>2</sup> PVC

Tipo contatto Type of contact	<b>Reed N.A./N.C. (SPDT)</b> Reed N.O./N.C. (SPDT)
Max potenza commut. Max switch. capacity	<b>80 W - (50 W SPDT)</b>
Max corrente commut. Max switch. current	<b>1 A - (1 A SPDT)</b>
Max tensione commut. Max switch. voltage	<b>250 Vac (220 Vac SPDT)</b>
Peso specif. liquido Specific fluid weight	<b>&gt; 0,75</b>
Temp. in funzionamento Working temperature	<b>-20°C / +100°C</b>
Peso Weight	<b>~ gr 85</b>